



### MINI LATHE

#### Specifications

Swing over bed		180 mm
Cross slide travel		65 mm
Motor output power		350 W
Distance between centers		350 mm
Hole through spindle		20 mm
Spindle taper		MT3
Tallstock taper		MT2
Spindle speed	Low range	100-1200 rpm±10%
	High range	100-3000 rpm±10%
Thread range	Metric version	0.4-2.0 mm (5 threads pitches)
	Imperial version	12-52 TPI (5 threads pitches)
Overall dimension (LxWxH)		880x290x290 mm
Weight (Net/Gross)		44/56 kg
Packing Size (LxWxH)		870x340x370 mm

#### Standard attachment

- 80mm 3-jaw Chuck
- MT2 Center
- Changing gear set
- Wrench set
- Oil can



#### Cutter 11 pieces set

- DIN 4971R DIN 4972R
  - DIN 4973R DIN 4974R
  - DIN 4975 DIN 4976
  - DIN 4977R
  - DIN 4978R
  - DIN 4980L
  - DIN 4980R
  - DIN 4981R
- 8X8mm S/N:10005



#### Quick change cutter rest



#### Rolling tailstock chuck



#### Cutter 6 pieces set

- DIN 4972R DIN 4973R
  - DIN 4974R DIN 4976R
  - DIN 4977R
  - DIN 4978R
- 8X8mm S/N:10006



#### Tailstock chuck



#### Mill chuck set



#### Cutter 5 pieces set

- DIN 4971R DIN 4975
  - DIN 4980R
  - DIN 4980L
  - DIN 4981R
- 8X8mm S/N:10004



#### Knurling tool holder



#### Wood toolrest with center



#### Digital spindle speed readout (independent using)



#### Cutter 2 pieces set



#### Cut-off tool



#### Rocker tool post



For mini Lathe C2

OPTIONAL ACCESSORIES