

MICRO MILL

Specifications

Drilling capacity	10 mm
End milling capacity	10 mm
Face milling capacity	16 mm
Headstock travel (Z)	230 mm
Cross axis (X)	90 mm
Longitudinal axis (Y)	180 mm
Throat	140 mm
Max. distance spindle to table	220 mm
Spindle taper	MT2
Motor output power	150 W
Spindle speed Low range	100-1000 rpm±10%
High range	100-2000 rpm±10%
Table effective size	240x145 mm
T-slot size	8 mm
Overall dimension (LxWxH)	425x350x690 mm
Weight (Net/Gross)	32/44 kg
Packing size (LxWxH)	420x395x625 mm

Standard attachment

Ø10 mm Drill chuck Wrench set Oil can



Oil tray for X1

Size 312 x 290mm
S/N:10106

SUPER X1

MICRO MILL

Specifications

Drilling capacity	10 mm
End milling capacity	10 mm
Face milling capacity	16 mm
Headstock travel (Z)	230 mm
Cross axis (X)	130 mm
Longitudinal axis (Y)	180 mm
Throat	140 mm
Head tilt	45°L, 45°R
Max. distance spindle to table	220 mm
Spindle taper	MT2
Motor output power	150 W
Spindle speed Low range	100-1000 rpm±10%
High range	100-2000 rpm±10%
Table effective size	240x145 mm
T-slot size	8 mm
Overall dimension (LxWxH)	500x350x690 mm
Weight (Net/Gross)	40/56 kg
Packing size (LxWxH)	530x400x630 mm

Standard attachment

Ø10 mm Drill chuck Wrench set Oil can




Oil tray for super X1

Size 455 x 316mm
S/N:10107

OPTIONAL A

Rotary table



Clamping kit



12pcs.

Bolt size 6mm

include: 2 studs,
1 step block pair,
2 T-nuts, 2 flange nuts,
2 coupling nuts, 2 end
holddowns

S/N:10104

Clamping kit



24 pcs.

Bolt size 6mm

include: 4 studs,
2 step block pairs,
4 T-nuts, 4 flange nuts,
4 coupling nuts,
4 end holddowns

S/N:10105

Stub milling machine arbor



for slitting saw, hole ø13mm
S/N:10116

Boring arbor with boring cutter



S/N:10117

