

ACCESSORIES

MINI MILLING MACHINE

Specifications

Drilling capacity	13 mm
End milling capacity	16 mm
Face milling capacity	30 mm
Headstock travel (Z)	180 mm
Cross axis (X)	100 mm
Longitudinal axis (Y)	220 mm
Throat	170 mm
Max. distance spindle to table	280 mm
Head tilt	45°L, 45°R
Spindle taper	MT3 or R8
Motor output power	350 W
Spindle speed	Low range 100-1100 rpm±10%
	High range 100-2500 rpm±10%
Table effective size	390x92 mm
T-slot size	12 mm
Overall dimension (LxWxH)	520x500x760 mm
Weight (Net/Gross)	50/68 kg
Packing size (LxWxH)	540x500x760 mm

Standard attachment

- Ø13 mm Drill chuck
- Wrench set
- Oil can



2 Flute HSS end mill



Mill chuck set



Indexable carbide end mill



Stub milling machine arbor



Auto feeder



Clamping kit



Quick vice



Mill chuck set



2 Flute HSS end mill



Indexable carbide end mill



vice



MT#3 collet



S/N:10127 Stub milling machine arbor MT#3, ø16mm (picture ref. S/N:10116)
S/N:10128 Boring arbor with boring cutter MT#3 (picture ref. S/N:10117)
S/N:10129 Stub milling machine arbor MT#3, ø16mm (picture ref. S/N:10118)
S/N:10094 Rotary table