

### SMALL MILL

#### Specifications

Drilling capacity		25 mm
End mill capacity		16 mm
Face mill capacity		50 mm
Spindle stroke		80 mm
Throat		230 mm
Max. distance spindle to table		380 mm
Spindle taper		MT3 or R8
Spindle speed	High range	100-2000 rpm±10%
	Low range	100-1000 rpm±10%
Table effective size		550x160 mm
T-slot size		12 mm
Table cross travel		145 mm
Table longitudinal travel		400 mm
Motor output power		600 W
Overall dimension (LxWxH)		760x720x930 mm
Weight (Net/Gross)		165/198 kg
Packing size (LxWxH)		840x820x1040 mm



Chuck guard with auto power off is an optional accessory S/N 10115

#### Standard attachment

- Ø16 mm Drill chuck
- Wrench set
- Oil can

### OPTIONAL ACCESSORIES

#### Rotary table

Size 100mm



S/N: 10094



Dividing Plate for S/N 10094

S/N: 10094-1

Tailstock for S/N 10094



S/N: 10094-2

#### Work table with angle



S/N: 10135

#### Quick Vice



Width 100mm

S/N: 10036

#### Mill chuck set



MT#3

Chuck dia. 4, 6, 8, 10, 12, 14, 16mm

S/N: 10037

#### Power feeder



S/N: 10141

#### Vice with angle

Width 100mm



S/N: 10142


#### Vice



S/N: 10109

Width 80mm

#### Clamping kit



42 pcs.

Bolt size:10mm  
include:12 studs, 6 step block pairs, 4 T nuts, 4 flange nuts, 4 coupling nuts, 6 end holdowns

S/N:10047

#### Indexable carbide end mill



MT#3  
ø30mm

S/N:10046